

AD-A041 079

BALLISTIC RESEARCH LABS ABERDEEN PROVING GROUND MD
RESPONSE OF THREE TYPES OF TRANSIENT COMBUSTION MODELS TO GUN P--ETC(U)
MAY 77 C W NELSON
BRL-MR-2752

F/G 19/1

NL

UNCLASSIFIED

1 OF 1


AD
A041 079



END

DATE
FILMED

7 - 77



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

BRL MR 2752

BRL

12
B.S.

AD

ADA041079


MEMORANDUM REPORT NO. 2752

(Supersedes IMR No. 447)

RESPONSE OF THREE TYPES OF TRANSIENT COMBUSTION MODELS TO GUN PRESSURIZATION

Carl W. Nelson

May 1977



Approved for public release; distribution unlimited.

USA ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
USA BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

AJ NO.
DDC FILE COPY

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report by originating
or sponsoring activity is prohibited.

Additional copies of this report may be obtained
from the National Technical Information Service,
U.S. Department of Commerce, Springfield, Virginia
22151.

NTIS	Reproduction	<input checked="" type="checkbox"/>
DDC	Unit Section	<input type="checkbox"/>
UNANNOUNCED		<input type="checkbox"/>
JUSTIFICATION		
BY DISTRIBUTION/AVAILABILITY CODES		
DISC.	AVAIL. DOC/OF	SPECIAL
A		

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MEMORANDUM REPORT NO. 2752 ✓	2. GOVT ACCESSION NO. (14) BRL-MR-2752	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Response of Three Types of Transient Combustion Models to Gun Pressurization	5. TYPE OF REPORT & PERIOD COVERED BRL Memorandum Report	
7. AUTHOR(s) Carl W. Nelson	6. PERFORMING ORG. REPORT NUMBER	
9. PERFORMING ORGANIZATION NAME AND ADDRESS U. S. Army Ballistic Research Laboratory Aberdeen Proving Ground, MD 21005	8. CONTRACT OR GRANT NUMBER(s)	
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Materiel Development & Readiness Command 5001 Eisenhower Avenue Alexandria, VA 22333	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 1T61102AH53	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	12. REPORT DATE May 1977	
	13. NUMBER OF PAGES 24	
	15. SECURITY CLASS. (of this report) Unclassified	
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES This report supersedes BRL Interim Memorandum Report No. 447, dated October 1975.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) solid propellant, transient combustion, burning rate, guns		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) Three types of models for transient solid propellant combustion are applied under an imposed pressure history of a 105mm tank gun. The three types are: (1) dp/dt dependence, (2) Quasi Steady Heat Feedback One Dimensional (QSHOD), and (3) Zeldovich. Each predicts a qualitatively different response for the same propellant thermal and thermodynamic properties under the same imposed pressure history.		

TABLE OF CONTENTS

	<u>Page</u>
LIST OF TABLES	5
LIST OF SYMBOLS.	7
I. INTRODUCTION	9
II. MODELS	10
$\frac{dp}{dt}$ Dependence Models	10
<u>Quasi Steady Heat Feedback One</u> <u>Dimensional (QSHOD)</u>	11
<u>Zeldovich Model</u>	12
<u>The Test Case</u>	13
III. RESULTS AND DISCUSSION.	13
IV. REFERENCES.	17
V. DISTRIBUTION LIST	19

LIST OF TABLES

	<u>Page</u>
Table I. Heat Feedback Terms.	12
Table II. Gas Production Ratios.	15

Preceding Page BLANK -

LIST OF SYMBOLS

A	pre-exponential constant for surface reaction (non-dim)
C_p	specific heat of gas
C_s	specific heat of solid
E	activation energy for surface reaction (non-dim)
H	heat feedback parameter (portion coming from exothermic pyrolysis)
m	burning rate parameter in KTSS model
n	burning rate pressure exponent
P	pressure
P_o	reference pressure
R	non-dimensional burning rate
r_o	steady state burning rate
T	temperature
T_o	initial propellant temperature
T_s	surface temperature
T_{so}	reference surface temperature
x	distance
z	pressure exponent in Kooker model
α	thermal diffusivity
Ω	constant in Kooker model
σ_p	temperature sensitivity of burning rate
θ_s	non-dimensional surface temperature
ψ	a constant coefficient

I. INTRODUCTION

Modeling the ignition and early combustion of a solid propellant granular bed has typically assumed that, once ignited, the regression rate depends only on the instantaneous gas pressure (usually $r=ap^n$). For lumped parameter gun codes, like Baer-Frankle¹, it has been the practice to adjust the two parameters (a , n) in the burning rate expression to induce an agreement between measured gun pressures and computed pressures. Such an adjustment process permits the burning rate to compensate to some degree for other errors in input data. Although the adjustments do permit parametric studies of gun performance, the disagreement with independent burning rate measurements prohibit the usefulness of the burning rate formula for any other gun.

Within the past five years, there have been several one-dimensional models of the flame spreading and combustion of the granular propellant bed. All these models use the same power law burning rate formulation as the lumped parameter models ($r=ap^n$). Until recently no serious consideration has been given to using other laws for burning rates probably because either no definitive solutions are available for the burning rate and/or the approximate models require too much additional computing. To date there have not even been approximations used to find a model's sensitivity to potential transient burning effects.

Considerable work has been directed to transient combustion of solid propellants in rocket motors. Emphasis has been on linear or nearly linear perturbations in chamber pressure oscillation or in extinguishment by depressurization. Kooker and Zinn² did a numerical investigation of the transient burning coupled to a solid rocket motor chamber by a nonlinear method and predicted some sharp burning rate transients with only small amplitude pressure oscillations. Recent work by Caveny et al³ attempted to model transient burning in gun conditions by using an approach due to Zeldovich for transient heat feedback to the propellant surface. Nonlinear models of the combustion

¹ P. G. Baer and J. M. Frankle, "The Simulation of Interior Ballistic Performance of Guns by Digital Computer Program", BRL Report No. 1183, December 1962 (AD #299980).

² D. E. Kooker and B. T. Zinn, "Numerical Investigation of Non-Linear Axial Instabilities in Solid Rocket Motors", BRL Contract Report No. 141, March 1974 (AD #776954).

³ L. H. Caveny, M. Summerfield, and C. W. Nelson, "Ignition Transients and Pressurization in Closed Chambers", 11th JANNAF Combustion Meeting, Pasadena, CA, CPIA Pub. 261, September 1974.

were developed by Krier et al⁴ and by Levine and Culick⁵. When Kooker and Nelson⁶ compared the predictions of the KTSS, Levine, and Kooker models in a typical gun pressure environment, they predicted that three models had the same qualitative response of a single sharp transient at a low pressure and an asymptotic approach to the power law representation as pressure increased.

It is the purpose of this brief report to compare the burning rate predictions of three different types of models for an imposed pressure history found in a typical Army gun.

II. MODELS

$\frac{dp}{dt}$ Dependence Models

Early approximations for the dynamic response were proposed by Paul et al⁷, Parker and Summerfield⁸ and vonElbe⁹. With some simplified analyses these researchers all arrived at a form for instantaneous burning rate:

$$r = r_o \left[1 + \psi \frac{n\alpha}{pr_o^2} \frac{dp}{dt} \right],$$

⁴ H. Krier, J. S. Tien, W. A. Sirignano, and M. Summerfield, "Nonsteady Burning Phenomena of Solid Propellants: Theory and Experiments" AIAAJ Vol. 6, No. 2, pp 278-285, February 1968.

⁵ J. N. Levine and F. E. C. Culick, "Nonlinear Analysis of Solid Rocket Combustion Instability", AFRPL TR-74-45, October 1974.

⁶ D. E. Kooker and C. W. Nelson, "Numerical Solution of Three Solid Propellant Combustion Models During a Gun Pressure Transient", 12th JANNAF Combustion Meeting, Newport, RI, August 1975.

⁷ B. E. Paul, R. L. Levine, and L. Y. Fong, "A Ballistic Explanation of the Ignition Pressure Peak", AIAA Solid Propellant Rocket Conference, Palo Alto, CA, AIAA Paper 64-121.

⁸ K. Parker and M. Summerfield, "The Ignition Transient in Solid Propellant Rocket Motors", Princeton University, Dpt. AMS Report 769, 1966.

⁹ G. vonElbe, "Solid Propellant Ignition and Response of Combustion to Pressure Transients, AIAA Paper 66-668, 1966.

where r_o steady state burning rate
 ψ_o a constant coefficient
 α thermal diffusivity
 n burning rate exponent
 P instantaneous pressure
 $\frac{dp}{dt}$ time derivative of pressure.

Krier¹⁰ briefly reviewed the derivations and their limitations to small changes from steady state operation. The coefficient ψ is different for each derivation (1/2 for Parker and Summerfield; 1 for Paul et al; 2 for vonElbe). Krier then relaxed the assumption of constant surface temperature and used the KTSS model of dynamic heat feedback to derive a variable expression for ψ :

$$\psi = \frac{(p/p_o)^{n/m} [1 - \frac{(p/p_o)^{n/m}}{m}]}{[(p/p_o)^{n/m} (2+1/n) - 2H]}$$

where P_o reference pressure
 m_o a constant
 H a non-dimensional surface heat release.

Quasi Steady Heat Feedback One Dimensional (QSHOD)

Three models solve the partial differential energy equation in the solid propellant using a nonlinear boundary condition at the propellant surface. Kooker and Nelson rederived the governing equations in a common coordinate system and compared the solutions for the pressure field in a 105mm tank gun as is the purpose of this report. The models all use a surface boundary condition of the form

$$\left. \frac{d\theta}{dx} \right|_o = G_1 R + G_2 / R ,$$

where $\frac{d\theta}{dx}$ non dimensional thermal gradient
 R non dimensional regression rate,

but differ in the form of the functions G_1 and G_2 and R . Table I gives the differences.

¹⁰ H. Krier, "Solid Propellant Burning Rate During a Pressure Transient", Comb Sci Tech Vol 5, pp 69-73, 1972.

Table I. Heat Feedback Terms

Model	G_1	G_2	R
KTSS	H	$p^{2n}(p^{n/m}-H)$	θ_s^m
Kooker/Zinn	$H+(\theta_s-1)(1-\frac{C_p}{C_s})$	$\Omega^2 \frac{C_p}{C_s} (\frac{T_{so}}{T_{so}-T_o})P$	$\exp[\frac{A(\theta_s-1)}{1+\frac{A}{E}(\theta_s-1)}]$
Levine/Culick	$H+(\theta_s-1)(1-\frac{C_p}{C_s})$	$p^{2n} \{ [\frac{C_p}{C_s} \frac{E}{A} (\frac{1}{1-\frac{n}{E} \ln P} -1)] + (1-H) \}$	$\exp[\frac{A(\theta_s-1)}{1+\frac{A}{E}(\theta_s-1)}]$

where θ non dimensional temperature
 c heat capacity
 T_{so} reference surface temperature
 A, E non dimensional kinetic constants.

The $G_1 R$ term represents heat from the exothermic surface reaction and $G_2 R$ represents heat from the flame. Kooker and Nelson found that the Kooker/Zinn and Levine/Culick models gave practically the same response and that the KTSS model predicted higher overshoots because of the presence of the $(\theta_s-1)(1-\frac{C_p}{C_s})$ term in the surface heat release term.

Zeldovich Model

Caveny et al used the Zeldovich approach to derive a nonsteady heat feedback of the form

$$\left. \frac{dT}{dx} \right|_0 = \frac{R}{\alpha} [T_s - \ln(\frac{R}{R_o}) / \sigma_p + T_o] ,$$

where σ_p temperature sensitivity.

The advantage gained is that no model of the flame need be specified. The non-steady heat feedback from the flame at $R(T_o, P)$ is assumed to be the same as the feedback at $R_o(R_{oeg}, P)$ when T_{oeg} is the initial temperature which would yield steady burning at $R(P)$. With that boundary condition, the thermal energy equation of the solid propellant is solved numerically.

The Test Case

A reference set of thermal and thermodynamic properties were assigned to a double base propellant. Best estimates from whatever experimental data were available were used. The only parameter which is observed to have a dramatic effect on the results is the value of the surface heat release in the QSHOD model group. Experimental data from Kubota et al¹¹ establish that the value can range easily from 70 to 100 cal/gm which corresponds to values of the parameter H from 0.58 to 0.83.

Temperature sensitivity for the propellant was measured as .0046/°K. To be consistent with the other parameters including H, a rough estimate of the temperature sensitivity may be obtained from Summerfield et al¹² as 0.0054/°K. One source of the difference is the derivation's assumption that the KTSS flame contribution to the heat feedback is independent of initial temperature. The difference carries no immediate impact because the results are essentially alike for either value.

The imposed pressure profile was that of the 105mm tank gun starting at 6.9 MPa where the propellant is assumed to be burning at steady state.

III. RESULTS AND DISCUSSION

The shapes of the burning rate response of the three types of models are distinctly different. Figure 1 plots the relative burning rate against time in a pressure field which rises almost linearly at an average rate of about 10^5 MPa/sec. For the models using surface heat release, it was assumed to be 96 cal/gm.

¹¹ N. Kubota, T. J. Ohlemiller, L. H. Caveny, and M. Summerfield, "An Experimental Study of the Site and Mode of Action of Platonizers in Double Base Propellants", AIAA Paper 74-124, January 1974.

¹² M. Summerfield, L. H. Caveny, R. A. Battista, N. Kubota, Yu A. Gostinsev, and H. Isoda, "Theory of Dynamic Extinguishment of Solid Propellants with Special Reference to Nonsteady Heat Feedback Law", *Journal of Spacecraft Rockets*, 8 (3), March 1971, pp 251-258.




Figure 1. Comparisons of Relative Burning Rates

Two values of ψ in the dp/dt model showed different results, although the same general shape. The Krier version reached a peak of 12.4 when the vonElbe version reached 17.4. The vonElbe curve was consistently higher than the Krier curve throughout the time examined. For the Krier version, the coefficient was initially about 1.5 and declined steadily to 0.7 at 0.5ms.

The QSHOD models all had the same shape which produced a sharp peak at 0.25ms. Peaks for the Levine/Culick and Kooker/Zinn were about the same at 6.1 but the KTSS peak was much higher at about 17 (not shown in Figure 1). Kooker and Nelson provide a more complete comparison for this type model.

For the Zeldovich model a much lower response was observed. The peak overshoot of only 2.1 occurred at 0.4ms.

In the computations, burning rate excursions did not affect the imposed pressure. In an actual chamber the two would be coupled because the faster gas generation rate would increase the pressurization rate. The mass of gas in the chamber is proportional to the integral $\int_0^t r_{rdt}$. To the extent that this integral exceeds the quasi-steady integral $\int_0^t r_o dt$, the chamber pressurization will be altered by the burning rate excursions. A rough estimate of the effect is given in Table II where the ratio $\int r_{rdt} / \int r_o dt$ is compared at different times. Translating the ratios into real chamber effects would require a coupling to the chamber dynamics.

Experimental verification of the magnitude of such burning rate excursion has not been made. Closed vessel tests of granular beds typically discard the low pressure information because of uncertainties in surface area and ignition spreading. Sharp spikes have been only occasionally reported and usually ignored as a test anomaly. An inference to be drawn is either the spikes do not occur or the time for flame spreading is of the same order as the time for the burning rate excursion. Resolution awaits better experimental information.

Table II. Gas Production Ratios

	<u>0.1ms</u>	<u>0.25ms</u>	<u>0.5ms</u>	<u>0.8ms</u>
$dp/dt \psi = 2$	13.1	7.10	3.91	2.47
$dp/dt \psi = f(p)$	9.0	4.75	2.64	1.79
Levine/Culick	0.97	2.16	1.81	1.52
Zeldovich	0.97	1.21	1.43	1.40

A serious criticism may be leveled at applying the QSHOD models to nitrocellulose based gun propellants. The derivation of the flame

contribution to the heat feedback assumes a uniform distribution of the energy release in the flame on the basis that composite propellant flames are diffusion controlled. Because nitrocellulose based propellants are avidly believed to have premixed, kinetically controlled, thin flames, the models must be reexamined to judge the effect of changing the flame structure. A quick calculation for a flame sheet approximation showed the overshoots to be more like the Zeldovich results. The true energy release distribution lies probably somewhere in between the two extremes with a reasonable conclusion that no clear case can be made for choosing between the Zeldovich and QSHOD models for a nitrocellulose based propellant.

The implications of this study are not limited to the particular problem chosen. The gun pressure profile selected, monotonic and nearly linear, is not strictly limited to guns. Two real cases can be conceived where the results are applicable: A gun with a composite propellant, like a nitramine base, or any other vessel like a rocket, with a composite propellant in a rapid pressurization. The message is clear: do not choose a model on the basis that they all give the same answer.

REFERENCES

1. P. G. Baer and J. M. Frankle, "The Simulation of Interior Ballistic Performance of Guns by Digital Computer Program", BRL Report No. 1183, December 1962, AD #299980.
2. D. E. Kooker and B. T. Zinn, "Numerical Investigation of Non-Linear Axial Instabilities in Solid Rocket Motors", BRL Contract Report No. 141, March 1974, AD #776954.
3. L. H. Caveny, M. Summerfield, and C. W. Nelson, "Ignition Transients and Pressurization in Closed Chambers", 11th JANNAF Combustion Meeting, Pasadena, CA, CPIA Pub. 261, September 1974.
4. H. Krier, J. S. Tien, W. A. Sirignano, and M. Summerfield, "Non-steady Burning Phenomena of Solid Propellants: Theory and Experiments", AIAAJ, Vol. 6, No. 2, pp 278-285, February 1968.
5. J. N. Levine and F. E. C. Culick, "Nonlinear Analysis of Solid Rocket Combustion Instability", AFRPL TR-74-45, October 1974.
6. D. E. Kooker and C. W. Nelson, "Numerical Solution of Three Solid Propellant Combustion Models During a Gun Pressure Transient", 12th JANNAF Combustion Meeting, Newport, RI, August 1975.
7. B. E. Paul, R. L. Levine, and L. Y. Fong, "A Ballistic Explanation of the Ignition Pressure Peak", AIAA Solid Propellant Rocket Conference, Palo Alto, CA, AIAA Paper 64-121.
8. K. Parker and M. Summerfield, "The Ignition Transient in Solid Propellant Rocket Motors", Princeton University, Dpt. AMS Report 769, 1966.
9. G. vonElbe, "Solid Propellant Ignition and Response of Combustion to Pressure Transients", AIAA Paper 66-668, 1966.
10. H. Krier, "Solid Propellant Burning Rate During a Pressure Transient", Comb Sci Tech Vol 5, pp 69-73, 1972.
11. N. Kubota, T. J. Ohlemiller, L. H. Caveny, and M. Summerfield, "An Experimental Study of the Site and Mode of Action of Platonizers in Double Base Propellants", AIAA Paper 74-124, January 1974.
12. M. Summerfield, L. H. Caveny, R. A. Battista, N. Kubota, Yu A. Gostinsev, and H. Isoda, "Theory of Dynamic Extinguishment of Solid Propellants with Special Reference to Nonsteady Heat Feedback Law", Journal of Spacecraft Rockets, 8 (3), March 1971, pp 251-258.

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Commander Defense Documentation Center ATTN: DCC-TCA Cameron Station Alexandria, VA 22314	1	Commander US Army Missile Research and Development Command ATTN: DRDMI-R Redstone Arsenal, AL 35809
1	Director Defense Advanced Research Projects Agency ATTN: C.R. Lehner 1400 Wilson Boulevard Arlington, VA 22209	1	Commander US Army Tank Automotive Development Command ATTN: DRDTA-RWL Warren, MI 48090
2	Director Institute for Defense Analyses ATTN: Dr. H. Wolfhard Mr. R.T. Oliver 400 Army-Navy Drive Arlington, VA 22202	2	Commander US Army Mobility Equipment Research & Development Command ATTN: Tech Doc Ctr, Bldg. 315 DRSME-RZT Ft. Belvoir, VA 22060
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDMA-ST 5001 Eisenhower Avenue Alexandria, VA 22333	1	Commander US Army Armament Materiel Readiness Command Rock Island, IL 61202
1	Commander US Army Aviation Systems Command ATTN: DRSAV-E 12th and Spruce Streets St. Louis, MO 63166	3	Commander US Army Frankford Arsenal ATTN: DRDAR-LCE-CI, Dr. J. Lannon SCA-CC, Mr. C. Dickey SCA-PP, Mr. L. Stiefel Philadelphia, PA 19137
1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035	3	Commander US Army Armament Research and Development Command ATTN: DRDAR-LC, Dr. J.P. Picard DRDAR-LCE, Mr. C. Lenchitz DRDAR-LCE, Dr. R.F. Walker Dover, New Jersey 07801
1	Commander US Army Electronics Command ATTN: DRSEL-RD Ft. Monmouth, NJ 07703	1	Commander US Army White Sands Missile Range ATTN: STEWS-VT WSMR, NM 88002

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander US Army Watervliet Arsenal ATTN: R. Thierry/Code SWEWV-RD Watervliet, NY 12189	2	Commander US Naval Surface Weapons Center ATTN: S.J. Jacobs/Code 240 Code 730 Silver Spring, MD 20910
1	Commander US Army Harry Diamond Labs ATTN: DRXDO-TI 2800 Powder Mill Road Adelphi, MD 20783	1	Commander US Naval Surface Weapons Center ATTN: Tech Lib Dahlgren, VA 22338
1	Commander US Army Materials and Mechanics Research Center ATTN: DRXMR-ATL Watertown, MA 02172	1	Commander US Naval Underwater Systems Center Energy Conversion Department ATTN: R.S. Lazar/Code 5B331 Newport, RI 02840
1	Commander US Army Natick Research and Development Command ATTN: DRXRE, Dr. D. Sieling Natick, MA 01762	2	Commander US Naval Weapons Center ATTN: Dr. R. Derr Mr. C. Thelen China Lake, CA 93555
1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SA WSMR, NM 88002	1	Commander US Naval Research Laboratory ATTN: Code 6180 Washington, DC 20375
1	Commander US Army Research Office ATTN: Tech Lib P.O. Box 12211 Research Triangle Park, NC 27706	3	Superintendent US Naval Postgraduate School ATTN: Tech Lib Dr. David Netzer Dr. Allen Fuhs Monterey, CA 93940
1	Chief of Naval Research ATTN: Code 473 800 N. Quincy Street Arlington, VA 22217	2	Commander US Naval Ordnance Station ATTN: Dr. A. Roberts Tech Lib Indian Head, MD 20640
1	Commander US Naval Sea Systems Command ATTN: J.W. Murrin (NAVSEA-0331) National Center, Bldg. 2, Rm 6E08 Washington, DC 20360	2	AFOSR ATTN: J.F. Masi Dr. B.T. Wolfson Bolling AFB, DC 20332

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
2	AFRPL (DYSC) ATTN: Dr. D. George Mr. J.N. Levine Edwards AFB, CA 93523	1	General Electric Company Armament Department ATTN: M.J. Bulman Lakeside Avenue Burlington, VT 05402
1	Lockheed Palo Alto Rsch Labs ATTN: Tech Info Ctr 3521 Hanover Street Palo Alto, CA 94304	1	General Electric Company Flight Propulsion Division ATTN: Tech Lib Cincinnati, OH 45215
1	Aerojet Solid Propulsion Co. ATTN: Dr. P. Micheli Sacramento, CA 95813	2	Hercules Incorporated Alleghany Ballistic Lab ATTN: Dr. R. Miller Tech Lib Cumberland, MD 21501
1	ARO Incorporated ATTN: Mr. N. Dougherty Arnold AFS, TN 37389	2	Hercules Incorporated Bacchus Works ATTN: Dr. M. Beckstead Dr. R. Simmons Magna, UT 84044
1	Atlantic Research Corporation ATTN: Dr. M.K. King 5390 Cherokee Avenue Alexandria, VA 22314	1	IITRI ATTN: Dr. M.J. Klein 10 West 35th Street Chicago, IL 60615
1	AVCO Corporation AVCO Everett Research Lab Div ATTN: D. Stickler 2385 Revere Beach Parkway Everett, MA 02149	1	Olin Corporation Badger Army Ammunition Plant ATTN: J. Ramnarace Baraboo, WI 53913
2	Calspan Corporation ATTN: Dr. E.B. Fisher A.P. Trippe P.O. Box 235 Buffalo, NY 14221	2	Olin Corporation New Haven Plant ATTN: R.L. Cook D.W. Riefler 275 Winchester Avenue New Haven, CT 06504
1	ENKI Corporation ATTN: M.I. Madison 9015 Fulbright Avenue Chatsworth, CA 91311	1	Paul Gough Associates, Inc. ATTN: Dr. P.S. Gough P.O. Box 1614 Portsmouth, NH 03801
1	Foster Miller Associates, Inc. ATTN: A.J. Erickson 135 Second Avenue Waltham, MA 02154		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Physics International Company ATTN: J.D. Watson 2700 Merced Street Leandro, CA 94577	2	Thiokol Corporation Wasatch Division ATTN: Dr. John Peterson Tech Lib P.O. Box 524 Brigham City, UT 84302
1	Pulsepower Systems, Inc. ATTN: L.C. Elmore 815 American Street San Carlos, CA 94070	1	TRW Systems Group ATTN: Dr. H. Korman One Space Park Redondo Beach, CA 90278
1	Science Applications, Inc. ATTN: Dr. R.B. Edelman 23146 Cumorah Crest Woodland Hills, CA 91364	2	United Technology Center ATTN: Dr. R. Brown Tech Lib P.O. Box 358 Sunnyvale, CA 94088
2	Rockwell International Corp. Rocketdyne Division ATTN: Dr. C. Obert Dr. J.E. Flanagan 6633 Canoga Avenue Canoga Park, CA 91304	1	Universal Propulsion Co. ATTN: H.J. McSpadden P.O. Box 546 Riverside, CA 92502
2	Rockwell International Corp. Rocketdyne Division ATTN: Mr. W. Haymes Tech Lib McGregor, TX 76657	1	Battelle Memorial Institute ATTN: Tech Lib 505 King Avenue Columbus, OH 43201
1	Shock Hydrodynamics, Inc. ATTN: Dr. W.H. Anderson 4710-16 Vineland Avenue North Hollywood, CA 91602	1	Brigham Young University Dept of Chemical Engineering ATTN: Prof. R. Coates Provo, UT 84601
1	Thiokol Corporation Elkton Division ATTN: E. Sutton Elkton, MD 21921	1	California Institute of Tech Jet Propulsion Laboratory ATTN: Prof. F.E.C. Culick Pasadena, CA 91103
3	Thiokol Corporation Huntsville Division ATTN: Dr. D. Flanagan Dr. R. Glick Tech Lib Huntsville, AL 35807		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Case Western Reserve Univ Division of Aerospace Sciences ATTN: Prof. J. Tien Cleveland, OH 44135	3	Princeton University Forrestal Campus Library ATTN: Dr. L. Caveny Prof. M. Summerfield Tech Lib P. O. Box 710 Princeton, NJ 08540
3	Georgia Institute of Technology School of Aerospace Engineering ATTN: Prof. B. T. Zinn Prof. E. Price Prof. W. C. Strahle Atlanta, GA 30332	2	Purdue University School of Mechanical Engineering ATTN: Prof. J. Osborn Prof. S.N.B. Murthy TSPC Chaffee Hall West Lafayette, IN 47906
1	Institute of Gas Technology ATTN: Dr. D. Gidaspow 3424 S. State Street Chicago, IL 60616	1	Rutgers State University Dept of Mechanical and Aerospace Engineering ATTN: Prof. S. Temkin University Heights Campus New Brunswick, NJ 08903
1	Johns Hopkins University Applied Physics Laboratory Chemical Propulsion Informa- tion Agency ATTN: Mr. T. Christian Johns Hopkins Road Laurel, MD 20810	1	Southwest Research Institute Fire Research Section ATTN: W. H. McLain P. O. Drawer 28510 San Antonio, TX 78228
1	Massachusetts Institute of Technology Dept of Mechanical Engineering ATTN: Prof. T. Toong Cambridge, MA 02139	1	Stanford Research Institute Propulsion Sciences Division ATTN: Tech Lib 333 Ravenswood Avenue Menlo Park, CA 94024
1	Pennsylvania State University Applied Research Lab ATTN: Dr. G. M. Faeth P. O. Box 30 State College, PA 16801	1	Stevens Institute of Technology Davidson Laboratory ATTN: Prof. R. McAlevy, III Hoboken, NJ 07030
1	Pennsylvania State University Dept of Mechanical Engineering ATTN: Prof. K. Kuo University Park, PA 16801	1	University of California, San Diego AMES Department ATTN: Prof. F. Williams P. O. Box 109 La Jolla, CA 92037

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>
1	University of Illinois Dept of Aeronautical Engineering ATTN: Prof. H. Krier Transportation Bldg, Rm 105 Urbana, IL 61801
1	University of Minnesota Dept of Mechanical Engineering ATTN: Prof. E. Fletcher Minneapolis, MN 55455
2	University of Utah Dept of Chemical Engineering ATTN: Prof. A. Baer Prof. G. Flandro Salt Lake City, UT 84112
<u>Aberdeen Proving Ground</u>	
Marine Corps Ln Ofc Dir, USAMSAA	